

UHF Adhesive Label


(Model: L0760202601U)

1. Performance Specifications


RFID Chip	Impinj M750		
Protocol	ISO/IEC 18000-6C, EPCglobal Class 1 Gen 2		
Operating Frequency	860~960MHz		
Operating Mode	Passive(Battery free)		
Memory	96 bit TID, 96 bit EPC, 32 bit User Memory	32Bits Share Access&Kill	
IC Life	100,000 Programming cycles, 10 years data retention		
Read distance	Average reading distance: 7m (Reader and Environment Dependent)		

2. Mechanical Dimensions

NO.	Item	Parameter(mm)	Tolerance	Parameter(in.)
A1	Antenna Width	70.00 mm	± 0.20 mm	2.756 in.
A2	Antenna Length	14.50 mm	± 0.20 mm	0.571 in.
C37	Label Width	76.00 mm	± 0.20 mm	2.992 in.
C38	Label Length	20.00 mm	± 0.50 mm	0.787 in.
C42	Label Pitch	22.23 mm	± 1.00 mm	0.875 in.
C47	Label Edge to Liner Edge (Top)	2.00 mm	± 1.50 mm	0.079 in.
C48	Label Edge to Liner Edge (Bottom)	2.00 mm	± 1.50 mm	0.079 in.
C53	Liner Width	80.00 mm	± 1.00 mm	3.150 in.
C60	Core inner diameter	76.20 mm	± 1.00 mm	3.000 in.
C61	Reel Outer diameter	≤ 203mm (Based on the actual shipment quantity)		
C62	Label Corner Radius	2.00 mm	± 0.20 mm	0.079 in.




3. Label Structure



Surface Material	White Art paper	80g/m ² ± 10%, 72μm ± 10%
Adhesive 1	Acrylic emulsion	16g/m ² ± 5g/m ²
Antenna	Aluminum etching	AL + PET (10μm + 50μm)
Adhesive 2	Acrylic emulsion	16g/m ² ± 5g/m ²
Release Paper	White glassine paper	80g/m ² ± 10%, 70μm ± 10%

4. RF Performance



5. Environment Requirement

Operating Temperature/Humidity	-0~60℃ / 20%~80% RH	
Storage Temperature/Humidity	20~30℃ / 20%~60% RH	
Shelf Life	1 year in anti-static bag at 20~30℃ / 20% ~60% RH	
ESD Voltage Immunity	2 kV (HBM)	
Bending Diameter	> 50mm	

6. Delivery Details

Appearance	Single row reel form	
Quantity	3000 ± 10 pcs/Roll; 4 Rolls/Carton	445x445x135mm
Weight	To be determined	
Final inspection	100 %, known faulty ones marked	
Delivery yield	≥ 99%	

Packaging
Photograph



Xingeshan reserves the right for modifying the specification data without notice in advance!

Nanning XinGeShan Electronic Technology Co., Ltd.
+86-0771-5816625 <https://www.xgsunrfid.com/>